



Better Chemistry. **Better Business.**

Aquastrip MPS

Product Code: 2572012
Revised Date: 5/13/2014

Aquastrip MPS

DESCRIPTION

Aquastrip MPS paint stripper is an alkaline liquid concentrate, used full strength at temperatures ranging from 100 °F to 180 °F to remove powder coat and acrylic coatings from all metal types. **Aquastrip MPS** is fast acting and free rinsing which accommodates further processing or an application of a final finish.

FEATURES AND BENEFITS

- Can be used on both ferrous and non-ferrous metals
- Quickly removes most paint films
- Free of chlorinated solvents, phenols, and acids
- Will not cause hydrogen embrittlement
- Removes most coating in sheets
- Contains non-hazardous solvents
- No flash point
- Can be used on most metals
- Biodegradable
- Easily filtered for extended bath life
- Does not contain Formic Acid

TYPICAL APPLICATIONS

- Removal of powder paints
- Removal of lacquers and urethane coatings
- Excellent choice for removing organic coating from aluminum



Better Chemistry. **Better Business.**

Aquastrip MPS

Product Code: 2572012
Revised Date: 5/13/2014

MATERIALS OF CONSTRUCTION

Steel or stainless steel tanks.

OPERATING CONDITIONS

(Soak Tank) – Concentration: Full strength
Temperatures: 100 °F to 180 °F
Time: As required
Agitation: Recommended

NOTICE

Before using this material, read and understand OSHA Material Safety Data Sheet for **Aquastrip MPS**. Specific instructions and precautions should be followed to assure correct use and personal safety.

TITRATION PROCEDURE

1. Pipette 2 ml sample into a 250 ml Erlenmeyer flask containing 50 ml of distilled water.
2. Add 5-10 drops of methyl orange/xylene cyanole indicator and mix.
3. Titrate with 0.5 N hydrochloric acid to a purple endpoint.

CALCULATION: Milliliters of 0.5 N HCl x 9 .09 = % by volume **Aquastrip MPS**

WASTE DISPOSAL

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.