

Purging Cleaner IPS-10

Sump Purging Cleaner

IPS-10 is a coolant & wash system purging cleaner which removes organic contaminants such as stinky mud and sludge, oils, fluids, silicones, release agents and other undesirable related materials. Provides oil splitting properties, reduces thickness and viscosity of fluids and allows for filtration, separation and emulsion splitting.

IPS-10 has an effective surface wetting and dispersant system which can effectively trap these contaminants into the cleaner and provide effective rinsing from the system. Neutralizes nasty odors and allows flushing of them from systems.

IPS-10 is free of caustic, compatible with all wash systems, free rinsing, biodegradable and non-phosphated. Low foam operating properties.

Features & Benefits

- Liquid concentrate which readily mixes disperses into water.
- Works fast, penetrating and encapsulating contaminants.
- Kills odors, cleans fast, lifts sludge, rinses free.
- Rinses freely from all surfaces.
- Penetrates contaminants and flushes system free of residue.
- Does not interfere with wastewater treatment systems.
- Effectively attacks silicones and waxes removing them from the system.

Physical Data

pH	12
Product Type	Liquid
Spec. Gravity	1.01
lbs./gal.	8.42
Foam, 0 = Low, 9 = High	1
Shelf-Life Years	10 years
Freeze Information	Not damaged by freezing.

Typical Processing

1. Use at a level of 3 - 10.0% (depending on load of soil in system) by volume to flush and clean system. Time: Circulate well. Allow 1/2 - 4 hours to effectively remove contaminants.
2. Temperature: ambient -140 F. is preferred. (or as needed in system)
3. Run filters and overflow mechanisms while processing purge.
4. Rinse system well with water.

Packaging

Container Type	Poly
Net Units	463
Tare Wt.	25 lb.
Gross Wt.	488
DOT_Name	Not regulated by D.O.T.
DOT Hazard	Not regulated.
Tariff ID	

Use Parameters

Concentration Range	3 – 10% typical.
Temperature Range	80 – 170 deg F.
Time Range	½ - 8 hours as available.
Agitation	Circulate spray.

Waste Disposal

Biodegradable.

Holding Tank Materials of Construction

Stainless, steel, or poly.

Other Information

It is important that the OSHA DATA, "Material Safety Data Sheet" be carefully read and reviewed with the users of this product. OSHA data is required to be posted in the work area by law.

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS



CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.

