

# Metal Guard® 560

The result of the latest advances in thin film rust preventive technology, **Metal Guard 560** is designed to be the final finish on an engineered black oxide coating where 150 to 200 hours of salt spray resistance is desired yet dimensional change cannot be tolerated. It is a solvent-based, water-displacing rust preventive, which can be applied by dipping, spraying or brushing and will displace moisture on the metal surface, leaving a continuous film of Metal Guard 560 in direct contact with the metal surface.

Metal Guard 560 is also used for protection against rust and corrosion on automobile parts and accessories, sewing machines, firearms, fasteners of all types, small gasoline engines, machine tools, dies, jigs, fixtures and metal stampings.

Metal Guard 560 meets Mil-C-16173 Grade 3 Specifications.

## Features & Benefits

Rapid water displacement	Improved corrosion protection
High flashpoint	Improved safety
Used at ambient temperature	Reduced energy cost
Low odor	Improved working environment

## Physical Data

Flash point	149°F
Specific gravity	0.839
Appearance and odor	Clear amber solution, non-viscous, solvent smell
Film Thickness	0.21 mils
Coverage	Approx. 2,400 ft <sup>2</sup> /gallon
Water Displacement Test	Mil Spec MIL-C-16173D, Grade 3
Corrosion Test	Mil Spec MIL-C-23411 and MIL-C-81309



## Typical Applications

- Final rust preventative after black oxide coatings
- Final rust preventative after machining or cleaning operations
- Final rust preventative after zinc or manganese phosphate coatings
- Parts may be dipped while they are still wet from final rinse stage, since the displaced water rapidly settles to the bottom of the tank where it is periodically drawn off

## Caution

Harmful or fatal if swallowed. Contains petroleum distillates. Use with adequate ventilation. Avoid prolonged or repeated contact with skin. If swallowed, do not induce vomiting. Call a physician immediately.

**WARRANTY:** HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

## Our People. Your Problem Solvers.

For more information on this process,  
please call us at 203.756.5521 or email: [techservice@hubbardhall.com](mailto:techservice@hubbardhall.com)

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**<sup>136</sup>