



Product Bulletin

Product Name: Meta-Coat Clear C-113

Product Code: 2508914

Revision Date: June 2, 2025

META-COAT CLEAR C-113

IDENTIFICATION LUBE COATING

META-COAT CLEAR C-113 is a water based metal and other surface identification / lubricant coating for use in applications where surface identification and lubrication is desired. Provides corrosion protection and clear glossy coatings.

Meta Coat Clear dries to a clear and durable glossy lubricant film. Applied in dip baskets, barrels or light spray systems. Water based, solvent free formulation provides safety to workers. Uncured coatings can be washed from the surface with simple alkaline wash.

Meta Coat Clear is used particularly on surfaces where glossy and clear color identification, light lubrication and corrosion resistance is desired. The durable film also provides for storage stain and rust protection to coated parts.

Features & Benefits

Removed by heavy duty alkaline washing or water blasting when necessary.
Applied to surfaces by simple dip, flooding, rolling or brooming over surface.

Air dries in short time at ambient temperature. Warm air blow is preferred.

SPECIAL NOTE: IT IS IMPORTANT TO ASSURE ACIDIC PH DOES NOT ENTER THE BATH. ACID PH WILL DESTROY THE COATING.

- Compatible for use on all paint and coating systems.
- Low use cost.
- Note: Also available in various colors.

Typical Processing

SMALL PARTS DIP SPIN COATERS:

Dilute product at 33% by volume with clean pure water. Clean tap water can be used. Coverage is 500-600+ sq. ft. per gallon.

Typically applied in dip spin coaters on small parts and fasteners'.
Surface dries rapidly depending on air circulation in area.
Collects airborne dust and dirt which cause coating failures.



Product Bulletin

Product Name: Meta-Coat Clear C-113

Product Code: 2508914

Revision Date: June 2, 2025

Specifications

pH	9-10
Prod._Type	Liquid459
Spc.Grav	1.0
LBS./GAL	8.34
FOAM 0=low 9=high	0
Shelf life years:	5 Years
Freeze information	Protect from freezing

Packaging

Container Type	POLY Drums
Net Units	458
Tare Wt.	25
Gross Wt.	483
Dot_Name	Not Regulated by D. O. T.
DOT Hazzard	Not Regulated
Tariff ID	1521.10.0040

Use parameters

Concentration Range	Use As Is or @ 25-50%
Range	Room Temp
Time Range	.5-24 Hours
Agitation	STIR

Other information

It is important that the **OSHA DATA, "Material Safety Data Sheet"** be carefully read and reviewed with the users of this product. OSHA data is required to be posted in the work area by law.

Waste Disposal

Contain and Dispose in accordance with local rules

Holding Tank Materials of Construction

Steel, Stainless or Poly.



563 South Leonard Street, Waterbury, CT 06708 • HubbardHall.com • 800-648-3412

Product Bulletin

Product Name: Meta-Coat Clear C-113

Product Code: 2508914

Revision Date: June 2, 2025

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.