

AquaPure™ DF-P

Aquapure DF-P is a non-silicone defoamer formulated for application as a tank side additive for metal working fluids, alkaline / acid-based cleaners or wastewater treatment chemicals. It will not haze or separate from the concentrate during storage. When used at the prescribed levels in process chemistry, Aquapure DF-P will not impair subsequent finishing operations such as painting or plating.

Features & Benefits

Non-silicone	Works well for foam control in process chemistry
Easy to use liquid	Can be added as a concentrate over tank side or added as a dilute solution on a continuous feed or foam control

Physical Data

Appearance	Opaque, off white
Specific gravity	8.2 – 8.4 lb/gallon
pH of a 50% solution	6.0 – 8.0
pH % non- volatile by weight	4.5 – 5.5

Typical Applications

- In process chemistry such as cleaners, pickles
- Waste treatment systems

Operating Conditions

A starting concentration of 1 pint to 100 gallons, (5 mL per gallon) of Aquapure DF-P. This amount can be increased or decreased, depending on the foam control required.



Caution

Store at room temperature. Freezing may reduce effectiveness of the product performance. If frozen, warm to room temperature and mix well before using.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.