

Demulsifier CC-1

Demulsifier CC-1 is designed to assist in separating water from a wide range of waste oils. This specialized blend of surface-active agents assists in the reduction in water content that increases the value of the oil by creating a more desirable fuel source.

Features & Benefits

Assists in separation of water from oil	Increases value of oil through separation of water
Easy to use, low to no odor	Liquid blend of surface-active ingredients
One product for all oils	Works on: Industrial, fuel and crankcase oils

Typical Applications

Typical oils treated with the Demulsified CC-1 include:

- Industrial Oils
- Fuel Oils
- Crankcase Oils

Operating Conditions

The Demulsifier CC-1 is typically added to a heated storage tank (160°F to 220°F) at a rate of 1 to 2 gallons per 1000 gallon of oil to be treated with good mixing. The treated tank is then allowed to stand without mixing for period (typically 12 to 24 hrs.) to allow the water to be separated to the bottom of the tank. The separated oil then is pumped out of the storage tank leaving a useable fuel oil.



Product Bulletin

Product Name: Demulsifier CC-1

Product Code: 2601200

Revision Date: May 27, 2025

WARRANTY: HUBBARD-HALL INC. IS NOT RESPONSIBLE FOR THE MISUSE, MISAPPLICATION, OR MISHANDLING OF THIS PRODUCT. SEE THE TERMS AND CONDITIONS OF SALE ON OUR WEBSITE FOR ADDITIONAL TERMS AND CONDITIONS CONCERNING OUR PRODUCTS, INCLUDING BUT NOT LIMITED TO, LIMITATIONS AND DISCLAIMERS OF WARRANTIES AND LIABILITIES.

Our People. Your Problem Solvers.

For more information on this process,
please call us at 203.756.5521 or email: techservice@hubbardhall.com

Hubbard-Hall holds certifications for **ISO 9001:2015**, Responsible Distribution, as accredited by the **ACD** (Alliance for Chemical Distributors) and as a **Women-Owned Small Business**, as well as maintaining an association with **Omni-Chem**¹³⁶.