

Aquastrip® MPS

Aquastrip MPS paint stripper is an alkaline liquid concentrate, used full strength at temperatures ranging from 100°F to 180°F to remove powder coat and acrylic coatings from all metal types. Aquastrip MPS is fast acting and free rinsing which accommodates further processing or an application as a final finish.

Features & Benefits

Safe on most metals	Replaces the need for multiple paint strippers
Easily filtered	Extended bath-life reduces cost

Typical Applications

- Removal of powder paints
- Removal of lacquers and urethane coatings
- Excellent choice for removing organic coating from aluminum

Operating Conditions

Soak Tank

Concentration	Full Strength
Temperature	100°F - 180°F
Time	As required
Agitation	Recommended
Materials of Construction	Use only 304 or 316 stainless steel tanks

Titration Procedure

1. Pipette 2 mL sample into a 250 mL Erlenmeyer flask containing 50 mL of distilled water.
2. Add 5 to 10 drops of Methyl Orange/Xylene Cyanole indicator and mix.
3. Titrate with 0.5 N Hydrochloric Acid to a purple endpoint.

Calculation

$$\text{Concentration} = \text{mL } 0.5 \text{ N HCl} \times 9.09$$



Cleaning
the Hard to Clean



Finishing
the Hard to Finish



Treating
the Hard to Treat

Waste Disposal

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

Caution

Before using this material, read and understand Safety Data Sheet for Aqastrip MPS. Specific instructions and precautions should be followed to assure correct use and personal safety.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our people. Your problem solvers.

For more information on this process please call us at
1-800-648-3412
or techservice@hubbardhall.com

