Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

Product Bulletin

Product Name: Aquastrip XCEL-WR Product Code: 2572019 Revision Date: January 19, 2021

Aquastrip® XCEL-WR

Aquastrip XCEL-WR is an alkaline liquid concentrate paint stripper, which is used full strength at temperatures ranging from 100°F to 180°F to remove powder coat, epoxy and acrylic coatings from all metal types.

Aquastrip XCEL-WR does NOT contain NMP.

Aquastrip XCEL-WR is fast acting and free rinsing, which accommodates further processing or as an application as a final finish.

Features & Benefits

Effective on both ferrous	Single product for various
and nonferrous metals	applications
Free of NMP, solvents,	Meets strict environmental
phenols and acids	regulations
Does not cause hydrogen	Retains integrity of metal parts
embrittlement	
Easily filtered	Extended bath life

Typical Applications

- Used in regions with strict environmental regulation
- Removal of powder, lacquers, and urethane coatings
- Excellent choice for removing organic coating from aluminum

Operating Conditions

(Soak tank)

Concentration	Full strength
Temperatures	100°F – 180°F
Time	As required
Agitation	Recommended

Tank Construction

Tanks should be used in reinforced polypropylene or 300 series stainless steel vessel.









Better chemistry. Better business.

Hubbard-Hall Inc. • 563 South Leonard Street, Waterbury, CT 07608 • HubbardHall.com • 800-648-3412

Product Bulletin

Product Name: Aquastrip XCEL-WR Product Code: 2572019 Revision Date: January 19, 2021

Titration Method

- Pipette 2 mL sample into a 250 mL Erlenmeyer flask containing 50 mL of distilled water.
- 2. Add 5 to 10 drops of Methyl Orange/Xylene Cyanole indicator and mix.
- 3. Titrate with 0.5 N Hydrochloric Acid to a purple endpoint.
- 4. Record mL used.

Calculation

Concentration = mL 0.5 N HCl x 9.508

Caution

Before using this material, read and understand OSHA Safety Data Sheet for Aquastrip XCEL-WR. Specific instructions and precautions should be followed to assure correct use and personal safety.

Waste Disposal

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our people. Your problem solvers.

For more information on this process please call us at 1-800-648-3412

or techservice@hubbardhall.com











