

Defoamer RS-2

Defoamer RS-2 is a milky white liquid product developed to defoam H-H resist strippers when they are used in spray machines. The foam generated in the spray stripping machine is primarily due to the stripped resists.

Features & Benefits

High activity (concentrated)	Low inventory footprint
Effective at low concentration	Economical, low cost of use
Stable	Long shelf life, less waste

Operating Conditions

Concentration	¼ pint to 1 quart per 100 gallons of made-up solution
---------------	---

Waste Disposal

This product, when discarded, is not a hazardous waste per federal regulations 40 CFR, PART 261. Disposal should be in accordance with applicable state and local ordinances for the disposal of industrial waste. Please check with local authorities for specific waste disposal in your area.

Waste Disposal

Defoamer RS-2 should be protected from freezing. Repeated freezing will cause thickening of the RS-2. Storing of Defoamer RS-2 at temperatures in excess of 115°F (46°C) will cause the Defoamer RS-2 to separate.

Defoamer RS-2 should be stored in an area which has a temperature of 50°F to 85°F. Under these temperature ranges the Defoamer RS-2 has a minimum of 6 months storage stability.



Cleaning
the Hard to Clean



Finishing
the Hard to Finish



Treating
the Hard to Treat

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

Our people. Your problem solvers.

For more information on this process please call us at

1-800-648-3412

or techservice@hubbardhall.com

