

# Aquapure<sup>®</sup> Quick Drop 651

Aquapure Quick Drop 651 is a one-component bentonite clay product specifically blended with a proprietary mixture of dry chemicals and a cationic polymer to treat a wide range of streams. The chemical, polymer, and clay mixture are time released when added to a waste stream. A series of sequential chemical reactions take place without operator intervention, saving time and labor. The entire treatment process is simplified by minimizing treatment steps and equipment needed.

## Features & Benefits

Encapsulates Contaminates	Produces non-leachable sludge
Specialty blend	Can remove FOG, TSS, and Metals
Polymer blended into product	One product for treatment
Strong filtrable floc formation	Easily dewatered resulting in drier filter cake

## Physical Data

pH (5% aqueous suspension)	11.3
Appearance	Granular solid, light tan to grey dry powder
Relative density	2.45 – 2.55
Bulk density (20°)	60 – 66 Lb/ft <sup>3</sup>

## Operating Conditions

Bench testing should be completed prior to using Aquapure Quick Drop 651 to ensure it is the optimal product for the wastewater system. An Aquapure Wastewater Specialist can complete this testing. Dosing will be determined based on the treatability study completed by the Aquapure Wastewater Specialist

## Caution

Wear proper protective clothing, eyewear and respirator when using. Do not breathe mist or dust. If contact is made with skin, flush with water. Refer to the Safety Data Sheet for more complete information.

WARRANTY: THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.

## Our people. Your problem solvers.

For more information on this process please call us at

1-800-648-3412

or [techservice@hubbardhall.com](mailto:techservice@hubbardhall.com)

