



AquaStrip XCEL

Product Code: 2572016
Revised Date: 4/25/2016

AquaStrip XCEL

DESCRIPTION

AquaStrip XCEL is an alkaline liquid concentrate paint stripper, which is used full strength at temperatures ranging from 100°F to 180°F to remove powder coat, epoxy and acrylic coatings from all metal types. **AquaStrip XCEL does NOT contain NMP.** **AquaStrip XCEL** is fast acting and free rinsing, which accommodates further processing or as an application as a final finish.

FEATURES AND BENEFITS

- Effective on both ferrous and non-ferrous metals
- Quickly removes most paint films
- Free of NMP, chlorinated solvents, phenols, and acids
- Will not cause hydrogen embrittlement
- Removes most coating in sheets
- Contains non-hazardous solvents
- Can be used on most metals
- Biodegradable
- Easily filtered for extended bath life
- Does not contain Formic Acid

TYPICAL APPLICATIONS

- Removal of powder paints
- Removal of lacquers and urethane coatings
- Excellent choice for removing organic coating from aluminum



Better Chemistry. **Better Business.**

Aquastrip **XCEL**

Product Code: 2572016
Revised Date: 4/25/2016

MATERIALS OF CONSTRUCTION

Steel or stainless steel tanks.

OPERATING CONDITIONS

(Soak Tank) – Concentration:	Full strength
Temperatures:	100° F to 180° F
Time:	As required
Agitation:	Recommended

NOTICE

Before using this material, read and understand OSHA Material Safety Data Sheet for **Aquastrip XCEL**. Specific instructions and precautions should be followed to assure correct use and personal safety.

TITRATION PROCEDURE

1. Pipette 2 ml sample into a 250 ml Erlenmeyer flask containing 50 ml of distilled water.
2. Add 5-10 drops of methyl orange/xylene cyanole indicator and mix.
3. Titrate with 0.5 N hydrochloric acid to a purple endpoint.

CALCULATION: Milliliters of 0.5 N HCl x 9.508 = % by volume **Aquastrip XCEL**

WASTE DISPOSAL

Assure conformity with applicable governmental regulations. Continue to observe precautions for volatile, combustible vapors from absorbed material.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.