



Product Bulletin

Better Chemistry. **Better Business.**

Demulsifier CC-1

Product Code: 2601200
Revised Date: March 19, 2015

Demulsifier CC-1

Demulsifier CC-1 is designed to assist in separating water from a wide range of waste oils. This specialized blend of surface active agents assists in the reduction in water content that increases the value of the oil by creating a more desirable fuel source.

Typical oils treated with the Demulsifier CC-1 include:

- Industrial Oils
- Fuel Oils
- Crankcase Oils

The Demulsifier CC-1 is typically added to a heated storage tank (160-220F) at a rate of 1 to 2 gallons per 1000 gallon of oil to be treated with good mixing. The treated tank is then allowed to stand without mixing for period of time (typically 12 to 24 hrs.) to allow the water to be separated to the bottom of the tank. The separated oil then is pumped out of the storage tank leaving a useable fuel oil.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.