



## Product Bulletin

*technicalservice@hubbardhall.com*

P.O. Box 790 • Waterbury, CT 06720-0790 • Tel: (203) 756-5521 • Fax: (203) 756-9017  
P.O. Box 969 • Inman, SC 29349-0969 • Tel: (864) 472-9031 • Fax: (864) 472-2117

### LUSTERLUME JM

2103057  
3/14/06

**LUSTERLUME JM** is an excellent burnishing compound for copper, brass and steel.

**LUSTERLUME JM** is used primarily for tumbling operations that require time cycles not more than 1 hour.

Concentration: Use **Lusterlume JM** at 1 oz. (8 grams/liter) per gallon of water.

Temperature: Room to 130°F.

#### **EQUIPMENT**

All types of burnishing equipment.

#### **WARRANTY**

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.