



## Product Bulletin

Better Chemistry. **Better Business.**

**Mi-Clean™ PW 16 LT**

**Product Code: 2003007**  
**Revised Date: 01/30/2006**

### **Mi-Clean™ PW 16 LT**

Powdered Low Temperature Alkaline Cleaner

**Mi-Clean™ PW 16 LT** is a blend of dry, free-flowing alkaline materials and biodegradable surfactants designed to promote efficient cleaning of a variety of soils from both ferrous and non-ferrous surfaces. It displays excellent rinsing and cleaning properties over relatively long periods of time.

**Mi-Clean™ PW 16 LT** is used at concentrations ranging from 1 to 4 ounces per gallon at temperatures of 120° to 150°F. The higher range of concentrations and temperatures are required for the more difficult cleaning problems.

**Mi-Clean™ PW 16 LT** may be maintained by frequent small additions depending on the volume of work processed as well as the type and amount of soil removed. For more precise control of solution strength, a simple chemical control method is available. When the **Mi-Clean™ PW 16 LT** cleaner solution becomes overly contaminated with soil it should be discarded. Where production is quite predictable, a schedule for solution life is easily determined.

Although **Mi-Clean™ PW 16 LT** contains less than 15% by weight sodium hydroxide, it is advisable to handle and work with this material as if it were predominantly sodium hydroxide.

When making additions of **Mi-Clean™ PW 16 LT** to working solutions, the **Mi-Clean™ PW 16 LT** should be added very slowly and cautiously to cool solutions (less than 110°F). Additions should be made using a small scoop or a shovel. It is not advisable to add product to working solution using pails or buckets.

When making up new solutions, **Mi-Clean™ PW 16 LT** should be added to cool water. Never add water to the powder.

### **TANK AND EQUIPMENT REQUIREMENTS**

Mild steel may be used for tanks and mild steel and stainless steel for heating coils or immersion heaters. Adequate ventilation should be provided.

**WARNING:** CORROSIVE TO SKIN AND EYES. DO NOT TAKE INTERNALLY.

In case of accidental skin or eye contact, flush freely with water for at least 15 minutes. Obtain medical attention. See WARNING label on drum.



## Product Bulletin

Better Chemistry. **Better Business.**

**Mi-Clean™ PW 16 LT**

**Product Code: 2003007**  
**Revised Date: 01/30/2006**

### WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.