



Better Chemistry. **Better Business.**

Ultrex Electro Cleaner HC

Product Code: 2001032
Revised Date: 05/05/2010

Ultrex Electro Cleaner HC
Multi Metal Electro Cleaner

Ultrex Electro Cleaner HC is a moderately alkaline electro cleaner, formulated especially for brass, copper alloys, lead alloys, steel, white metal and zinc. It's formulation provides for effective anodic conditioning, preparing the base metal for additional processing in a wide range of plating cycles.

SPECIAL FEATURES

- Buffered to Prevent Tarnish & Etching of Sensitive Metals
- Particularly Effective on Soldered Parts & Multi Metal Components
- Reserve Detergency for Standard Soak Cleaning Requirements
- Stable, Light Foam Blanket Prevents Corrosive Misting
- Keeps Polypropylene Barrels Clean

RECOMMENDED APPLICATION ELECTRO CLEANER

	Range	Optimum
Concentration (all metals)	4-8 oz/ gal (30-60 g/l)	6 oz/gal (45 g/l)
Temperature	140-180 deg F (60-82 deg C)	160 deg F (71 deg C)
Current Density (anodic)	10-50 ASF	As required
Voltage	3-6	As required
Time	2-5 minutes	As required
Agitation	Solution movement or mild air	As required



Product Bulletin

Better Chemistry. **Better Business.**

Ultrex Electro Cleaner HC

Product Code: 2001032
Revised Date: 05/05/2010

SOAK CLEANER BRASS & COPPER ALLOYS

	Range	Optimum
Concentration	4-10 oz/gal (30-75 g/l)	7 oz/gal (52.5 g/l)
Temperature	140 – 180 deg F (60-82 deg C)	160 deg F (71 deg C)
Time	2-5 minutes	As required
Agitation	Solution movement or air	As required

EQUIPMENT

Tank	Mild steel, reinforced polypro, or fiberglass
Heater	Steel coil, steel immersion type, steam fed, or gas fired
Ventilation	Mechanical to maintain levels below permissible exposure limits
Agitation	Stirrer, pump, work movement, or mild air

SOLUTION MAKE UP

Be sure the process tank has been drained and cleaned. Fill to within two thirds of final operating volume with clean, warm water (100-120 deg F, 38-49 deg C). With good solution stirring, gradually add the required amount of **Ultrex Electro Cleaner HC**. Rapid additions may result in localized boiling and spattering!

After the required amount of **Ultrex Electro Cleaner HC** has been added and dissolved, adjust final solution operating volume and temperature.

ANALYSIS PROCEDURE

As Electro Cleaner: The alkaline components are typically consumed in the electrolysis process. Surfactants and detergents are consumed in the cleaning process by emulsifying oils and grease. Drag out of the cleaner bath and replenishment of the bath with water also dilutes the working solution. In double cleaning cycles, drag in of acid into the second electro cleaner will neutralize some of the alkalinity. Regular maintenance additions of **Ultrex Electro Cleaner HC** are recommended to replenish the bath. This can be accomplished by observing quality of cleaning &

2

info@hubbardhall.com

P.O. Box 790 • Waterbury, CT 06720-0790 • Tel: (203) 756-5521 • Fax: (203) 756-9017
www.hubbardhall.com



Product Bulletin

Better Chemistry. **Better Business.**

Ultrex Electro Cleaner HC

Product Code: 2001032
Revised Date: 05/05/2010

conditioning and making appropriate additions per requirements of the particular process. Alternatively, the cleaner bath can be analyzed to determine actual concentration of **Ultrex Electro Cleaner HC** and the required addition of product to restore the balanced ratio of all the cleaner components.

As Soak Cleaner: The surfactants and detergents are consumed in the cleaning process by emulsifying oils and grease. Alkaline components are used up in the cleaning process, such as by saponifying fatty acids. Drag out of the cleaner bath also depletes these active components. Regular maintenance additions of **Ultrex Electro Cleaner HC** are recommended to replenish the bath. This can be accomplished by observing quality of cleaning and making appropriate additions per requirements of the particular process. Alternatively, the cleaner bath can be analyzed to determine actual concentration of **Ultrex Electro Cleaner HC** and the required addition of product to restore the balanced ratio of all the cleaner components.

The following analysis procedure is recommended:

1. Pipette a 5 milliliter sample of the cleaner bath into a 250 milliliter Erlenmeyer flask.
2. Add 50-100 milliliters of clean water.
3. Add 2-4 drops of Phenolphthalein Indicator to develop a pink solution color.
4. Titrate with 0.10 Normal Hydrochloric or Sulfuric Acid (titrant) just until the pink color has been discharged.

Calculation: (milliliters of titrant) X 0.597 = **Ultrex Electro Cleaner HC** oz/gal)

PROCESS SUGGESTIONS

Ultrex Electro Cleaner HC provides good emulsifying soak cleaning action. On cooling, some of the oils will be released. Therefore skimming the cleaner to remove oils is recommended. Solutions of **Ultrex Electro Cleaner HC** are also compatible with coalescers and oil removal filters. At some point during the bath life, the buildup of oil and grease contaminants will effectively saturate it, beyond which maintenance additions or filtration will not maintain desired performance. When this occurs, the cleaner should be dumped and a fresh solution prepared. The Technical Center or your Hubbard Hall Inc. sales representative will be glad to help determine optimum bath life.

Ultrex Electro Cleaner HC working solutions are buffered to protect sensitive metals from tarnish and etching. For optimum results the suggested operating ranges for electro cleaning are recommended.



Product Bulletin

Better Chemistry. **Better Business.**

Ultrex Electro Cleaner HC

Product Code: 2001032
Revised Date: 05/05/2010

Hexavalent chromium contamination (only 30 ppm) will also shorten the cleaner bath service life. Additions of Enerox™ Chrome Reducer CEH will efficiently reduce chrome to its trivalent state, precipitating it as Cr(III) Hydroxide, thereby extending cleaner life. Although tolerance of copper, iron, nickel, and zinc are high, sufficient loadings of these contaminants will result in deposition of a black smut. When this occurs the electro cleaner bath should be replaced with a fresh make up.

Because of its free rinsing characteristics, **Ultrex Electro Cleaner HC** is particularly suited for systems where rinsing facilities are marginal. It can be used separately as a soak and electro cleaner or perform both functions in the same process tank. **Ultrex Electro Cleaner HC** is soap free. Therefore no residues are left on cleaned surfaces. With proper post rinsing, parts entering the electro cleaner should be water break free. **Ultrex Electro Cleaner HC** is a good complement to ULTREX SOAK CLEANER HC (see technical data bulletin).

PHYSICAL CHARACTERISTICS

Appearance	Free flowing, white to off-white powder
Odor	Slight
Dusty	No
Foaming Tendency	Moderate
Maximum Solubility	32 oz/gal at 180 deg F (240 g/l at 82 deg C)

PRODUCT PROFILE

Caustic	Yes
Phosphate	No
Silicate	Yes
Complexors (Gluconate type)	No
Chelates (EDTA, NTA types)	No

HAZARD CLASSIFICATION

DOT Classification	8 (Corrosive Material)
DOT Shipping Name	Corrosive Solid, Basic Inorganic N.O.S.*
UN Number	1498
Packing Group	II
Guide Number	154

*Sodium Metasilicate



Product Bulletin

Better Chemistry. **Better Business.**

Ultrex Electro Cleaner HC

Product Code: 2001032
Revised Date: 05/05/2010

WASTE TREATMENT & DISPOSAL

Ultrex Electro Cleaner HC and its working solutions are alkaline. They may be neutralized with acid to meet local POTW or municipal effluent discharge requirements. Sludges and oils should be separated out before discharge. Spent **Ultrex Electro Cleaner HC** solutions may contain dissolved metals from the cleaning process. Therefore, additional treatment of the solution may be required to meet discharge requirements.

SAFETY INFORMATION

Please read and understand the **Ultrex Electro Cleaner HC** Material Safety Data Sheet before handling and using this product.

Recommended safety procedures for **Ultrex Electro Cleaner HC** tank make up are described on page 1 of the Technical Data bulletin.

WARRANTY

THE QUALITY OF THIS PRODUCT IS GUARANTEED ON SHIPMENT FROM OUR PLANT. IF THE USE RECOMMENDATIONS ARE FOLLOWED, DESIRED RESULTS WILL BE OBTAINED. SINCE THE USE OF OUR PRODUCTS IS BEYOND OUR CONTROL, NO GUARANTEE EXPRESSED OR IMPLIED IS MADE AS TO THE EFFECTS OF SUCH USE, OR THE RESULTS TO BE OBTAINED.